

Pump-Unit

PS 100-E-A-45



Technical Data

Drive Electro-hydraulic
 Drive Power 15,0 kW
 Total Power Consumption approx. 16,0 kW


Connections
 Electrical CEE 63 A / 400 V AC, 50 Hz, IP 54

In-/Outlets
 Suction line 1 x SK 50 MT - DN 50
 Pressure line G 1 BSPP IG DN 25 - RD 38
 Circulation line G 1 BSPP IG DN 25 - RD 32

Dimensions (L x W x H) 2.270 x 740 x 2.180 (mm)
 Weight approx. 1.500 kg

Application Pumping of cement-, fly ash and bentonite suspensions at anchoring, groutings, flushings, sealings, piling and vibrating jobs

Delivery Pump
 Pressure max. 100 bar¹⁾
 [max. 1.450 psi]¹⁾
 Flow rate max. 170 l/min.¹⁾
 [max. 45 gal U.S.]¹⁾



Pump-Unit PS 100-E-A-45



Standard Features

Framework

skid steel frame, partially enclosed and with partition panel, floor and oil pan, central towing device, fork lift guides lengthwise and crosswise, machine room sound proofed, lockable doors, finishing 2K-paint RAL 5005 (signal blue) or on customer desire unicoloured

Electric Drive

electric motor 15,0 kW, 1.500 rpm, 400 V AC, 50 Hz, IP 54, automatic phase correction, motor safety switch, control voltage 24 V DC (for valves and remote control), operating hour meter

Hydraulic

oil tank volume 170 l [45 gal U.S.], axial piston pump, oil cooler with thermostat, main oil filter, oil filling and ventilation filter, electrical oil filter pollution control, oil level and temperature indicator, manometer for hydraulic pressure, pressure and flow infinitely variable

Delivery Pump

vertical two-plunger pump \varnothing 100 mm, flow rate per double stroke $V = 2,8$ l [0,74 gal U.S.], pump valves (suction- and pressure line) self-acting (ball valves), circulation and pump-down valves manually actuated, flow rate adjustment electro-proportional, manual grease system for plunger sealing sleeves and manually with plunger oil, protective grid with safety function (pump shutdown)

Delivery Pressure Measurement

manometer 0-100 bar [1.450 psi] \varnothing 100 mm completely with stainless steel membrane

Operating Devices

main switch, control lights CURRENT POWER, CONTROL VOLTAGE and OIL COOLER OPERATION, warning lights EMERGENCY STOP ACTIVATED, OIL FILTER PUMP and OIL COOLER MALFUNCTION, buttons HYDRAULIC MOTOR ON/OPERATION and HYDRAULIC MOTOR OFF/MALFUNCTION, buttons EMERGENCY-STOP (2x), buttons PUMP ON and PUMP OFF, switch REMOTE CONTROL ON/OFF, switch HAND / AUTOMATIC, button AUTOMATIC START/STOP, switch LIGHT ON/OFF for LED rod lamp inside, rotary knob for max. DELIVERY PRESSURE adjustment, potentiometer FLOW RATE, flow rate counters l/min. [gal U.S./min.] and l/total [gal U.S./total] with zero-setting (2x), auto pre-select counter for flow rate l/total [gal U.S./total], **Connection Options:** socket REMOTE CONTROL with EMERGENCY-STOP bridge plug, free socket 400 V / 16 A, free socket 230 V / 16 A

Accessories (included)

documentation, special tools for operation and maintenance, cable remote control 15 m and cable reel 100 m, suction hose 3 m, circulation hose, corded LED rod lamp inside

Accessories (optional)

spare part kits, grouting hoses, suction hoses, fittings, grouting grippers

Supplementary Devices

mixing and storing tanks for solid suspensions, dosing devices, screw-conveyors, radio remote control, control devices, electronic data acquisition and recording, regulating and measuring systems RMS with computer evaluation per USB and injection journal, flow meter with delivery pressure measuring, electronic delivery pressure devices (pressure transmitter) at injection place, devices for radio data transmission

Further devices, special equipments and accessories on request!